


Fitting accessories


40-501 Silencer male thread, sintered bronze



Model-no.	T	L	A	E
40-501-M5*	M5	10	5	SW8
40-501-18	G1/8	16	6	11
40-501-14	G1/4	19	8	14
40-501-38	G3/8	28	8	18
40-501-12	G1/2	33	10	24
40-501-34	G3/4	53	12	30
40-501-100	G1	54	15	38


*Ms-thread and Sechskant

40-502 Silencer male thread, sintered bronze and brass




Model-no.	T	L	A	H
40-502-M5	M5	5	5	8
40-502-M7	M7	5.5	5	10
40-502-18	G1/8	6	6	12
40-502-14	G1/4	8.5	8	16

40-503 Silencer male thread, sintered bronze and brass



Model-no.	T	L	A	E
40-503-M5	M5	15	6	8.5

40-90 Silencer male thread, plastic



Model-no.	T	L	A	Ø H
40-90-018	G1/8	28	7	15.5
40-90-014	G1/4	35.5	7	19.5
40-90-038	G3/8	47	11.5	24.5
40-90-012-01	G1/2	47	10.5	24.5
40-90-034-01*	G3/4	97	18	48
40-90-100-01*	G1	97	18	48


* operating pressure max. 6 bar

Fitting accessories

40-271

Double nipple

male thread, brass nickel-plated




Model-no.	T	L	A	H
40-271-M5	M5	11.5	4	8
40-271-18	G1/8	16.5	6	13
40-271-14	G1/4	21	8	17
40-271-38	G3/8	23	9	19
40-271-12	G1/2	25.5	10	24

40-272

Double nipple, reducer

male thread, brass nickel-plated




Model-no.	T1	T2	L	A	B	H
40-272-M5-18	M5	G1/8	14.5	4	6	13
40-272-18-14	G1/8	G1/4	19	6	8	17
40-272-18-38	G1/8	G3/8	20	6	9	19
40-272-18-12	G1/8	G1/2	21.5	6	10	24
40-272-14-38	G1/4	G3/8	22	8	9	19
40-272-14-12	G1/4	G1/2	23.5	8	10	24
40-272-38-12	G3/8	G1/2	24.5	9	10	24

40-273

Reducing nipple


male / female thread, brass nickel-plated



Model-no.	T1	T2	L	A	H
40-273-M5-18	M5	G1/8	14	4	13
40-273-18-18	G1/8	G1/8	16	6	13
40-273-18-14	G1/8	G1/4	19	6	17
40-273-18-38	G1/8	G3/8	20	6	19
40-273-18-12	G1/8	G1/2	24	6	24
40-273-14-14	G1/4	G1/4	21	8	17
40-273-14-38	G1/4	G3/8	22	8	19
40-273-14-12	G1/4	G1/2	26	8	24
40-273-38-38	G3/8	G3/8	23	9	19
40-273-38-12	G3/8	G1/2	27	9	24
40-273-12-12	G1/2	G1/2	28	10	24


Fitting accessories

40-274 Reducing nipple female / male thread, brass nickel-plated




Model-no.	T1	T2	L	A	H
40-274-18-M5	G1/8	M5	10.5	6	13
40-274-14-18	G1/4	G1/8	13	8	17
40-274-38-18	G3/8	G1/8	14	9	19
40-274-12-18	G1/2	G1/8	15.5	10	24
40-274-38-14	G3/8	G1/4	14	9	19
40-274-12-14	G1/2	G1/4	15.5	10	24
40-274-12-38	G1/2	G3/8	15.5	10	24

40-275 Sleeve female thread, brass nickel-plated




Model-no.	T	L	H
40-275-M5	M5	10	8
40-275-18	G1/8	15	13
40-275-14	G1/4	21	17
40-275-38	G3/8	23	19
40-275-12	G1/2	30	24

40-276 Reducing sleeve female thread, brass nickel-plated



Model-no.	T1	T2	L	A	H
40-276-M5-18	M5	G1/8	13	5	13
40-276-18-14	G1/8	G1/4	18.5	8	17
40-276-18-38	G1/8	G3/8	19.5	8	19
40-276-18-12	G1/8	G1/2	23	8	24
40-276-14-38	G1/4	G3/8	22	10.5	19
40-276-14-12	G1/4	G1/2	25.5	10.5	24
40-276-38-12	G3/8	G1/2	26.5	11.5	24


40-277 Plug male thread, brass nickel-plated



Model-no.	T	A	L	H
40-277-M5	M5	4	7.5	8
40-277-18	G1/8	6	10.5	13
40-277-14	G1/4	8	13	17
40-277-38	G3/8	9	14	19
40-277-12	G1/2	10	15.5	24


Fitting accessories

40-278 Plug
taper male thread, brass




Model-no.	T	L	H
40-278-18	R1/8	5	5
40-278-14	R1/4	7.5	7

40-279 Plug
male thread, brass




Model-no.	T	L	A	øE	H
40-279-18	G1/8	11	8	14	5
40-279-14	G1/4	15	12	18	6
40-279-38	G3/8	15	12	22	8
40-279-12	G1/2	18	14	25	10

40-279-1 Plug
40-M79-1 male thread with O-ring, brass nickel-plated



Model-no.	T	L	A	øE	H
40-M79-1-M5	M5	7.5	4.5	8	2.5
40-M79-1-18	G1/8	9.5	6	14	5
40-M79-1-14	G1/4	11.5	7.5	17	6
40-279-1-38	G3/8	22	7.5	22	8
40-279-1-12	G1/2	25	9.5	25	10

40-251 Elbow connector
male / female thread, brass nickel-plated




Model-no.	T1	T2	L	A	E
40-251-M5	M5	M5	13	4	9
40-251-18	G1/8	G1/8	21	6	14
40-251-14	G1/4	G1/4	27	8	18

Fitting accessories

40-252

Cross manifold

female thread, M5 brass nickel-plated, G1/8 - G1/2 aluminium




Model-no.	T	øF	B	L
40-252-M5	M5	3.3	11	18
40-252-18	G1/8	4.5	17	25
40-252-14	G1/4	5.5	26	40
40-252-38	G3/8	5.5	34	50
40-252-12	G1/2	5.5	34	50

40-253

T-connector

male / female thread, brass nickel-plated




Model-no.	T1	T2	L	A	E
40-253-M5	M5	M5	13	4	9
40-253-18	G1/8	G1/8	21	6	14
40-253-14	G1/4	G1/4	27	8	18

40-254

Double nipple. adjustable

taper male thread, brass




Model-no.	T1	T2	L	A	B	H1	H2
40-254-18-18	R1/8	R1/8	27	9.2	9	15	5
40-254-18-14	R1/8	R1/4	30	12	12	15	5
40-254-14-14	R1/4	R1/4	33.5	12	12	19	6
40-254-38-38	R3/8	R3/8	36.5	13	13	22	8
40-254-12-12	R1/2	R1/2	44	16	16	27	12

40-254-1

Double nipple. adjustable

male thread with O-ring, brass nickel-plated



Model-no.	T1	T2	L	A	B	H1	H2
40-254-1-18-18	G1/8	G1/8	30	5.5	5.5	19	5
40-254-1-14-14	G1/4	G1/4	37	7.5	7.5	22	6
40-254-1-38-38	G3/8	G3/8	39.5	7.5	7.5	27	8
40-254-1-12-12	G1/2	G1/2	46	9.5	9.5	30	12