


Technical details

Connection	M5
Nominal size	3,2 mm
Temperature range	-10°C ... +70°C (-10°C...+60°C for use in ATEX areas)
Medium	Filtered, oil-free and dried compressed air according to ISO 8573-1:2010, Class 7:2:4, instrument air, free of aggressive additives. Differing the pressure dew point must be at least 10°C below lowest occurring ambient temperature.
Materials	Body: Al (anodized), seals: NBR and POM, inner parts: Al, brass, stainless steel
	Products without their own potential ignition source in accordance with Directive 2014/34/EU, suitable for use in hazardous areas (page 03)




Pneumatically operated spool valve. The valve switches upon pressurization of the pilot port.

3/2-way-valves



- L-25-310
3/2-way, single pilot, air spring return
- L-25-311
3/2-way, single pilot, mechanical spring return
- L-25-320
3/2-way, double pilot



5/2-way-valves



- L-25-510
5/2-way, single pilot, air spring return
- L-25-511
5/2-way, single pilot, mechanical spring return
- L-25-520
5/2-way, double pilot

Technical data


Model-no.:	L-25-310	L-25-311	L-25-320	L-25-510	L-25-511	L-25-520
Operating pressure (bar)	2 ... 10	1 ... 10	0 ... 10	0 ... 10	2 ... 10	0 ... 10
Pilot pressure (bar)	see diagram	see diagram	2 ... 10	see diagram	3 ... 10	2 ... 10
Flow rate (NI/min)	160	160	160	160	160	160
Weight (kg)	0.065	0.065	0.068	0.084	0.084	0.085




Series L-25

Dimensions


L-25-3xx




L-25-510



L-25-511



L-25-520



- 1 = pressure inlet
- 2,4 = outlets
- 3,5 = exhausts
- 10,12,14 = pilot ports

Explosion-proof equipment without inherent potential ignition sources

The articles listed in the appendix do not fall into the scope of the EU Directive 2014/34/EC. They are not subjected by Article 1 (2) and (3) of Directive 2014/34/EC. It has been proven by an ignition risk analysis that the valves have no potential ignition source of their own. They can be used in compliance with the requirements of e.g. DIN EN 1127-1:2019, DIN EN IEC 60079-0:2019, DIN EN ISO 80079-36:2016 and DIN EN ISO 80079-37:2016 in

Zone 1 explosion groups IIA, IIB and IIC, Zone 21 explosion groups IIIA, IIIB and IIIC
Zone 2 explosion groups IIA, IIB and IIC, Zone 22 explosion groups IIIA, IIIB and IIIC

The valves are not marked within the meaning of the ATEX Directive. They have to meet the requirements of the existing zones.

Available valves

Series	Versions
L-25	310, 311, 320, 511, 520



The operating instructions for the valve and the electrical equipment must be taken into account before putting into operation. These are included with each valve and are available at www.airtec.de.